



Referência Multicor ISO e ABNT	Passo P	Largura entre Placas W	Diâmetro do Rolo D	PINO				Passo Trans- versal C	PLACA		Carga de Ruptura		Carga de Trabalho máx. kgf	Peso aproxi- mado kg/m
				Diâmetro D	Comprimento E	Comprimento F	Comprimento L		Espessura T	Altura H	kgf ANSI	kgf TC		
04B-1	6	2,80	4,00	1,85	6,80	7,80	-----	-----	0,6	5	300	320	66	0,11
05 B-1	8	3,00	5,00	2,31	8,20	8,90	-----	-----	0,8	7,1	500	590	110	0,20
06B-1 06B-2 06B-3	9,525	5,72	6,35	3,28	13,15 23,40 36,40	14,10 24,40 39,50	----- ----- -----	10,24	1,3	8,2	900 1690 4750	1040 1870 5780	198 371 1045	0,41 0,77 2,03
081-410 082-408	12,70	3,175 2,38	7,77 3,30	3,60 3,60	9,398 7,79	10,59 -----	----- -----	----- -----	1 1	9,4 7,8	760 760	760 760	130 130	0,28 0,25
08B-1 08B-2 08B-3	12,70	7,75	8,51	4,45	16,70 31,20 45,10	18,20 32,20 46,10	18,50 32,50 46,40	13,92	1,6	12	1820 3180 4750	1940 3500 5780	364 636 950	0,69 1,34 2,03
10B-1 10B-2 10B-3	15,875	9,65	10,16	5,08	19,50 36,10 52,70	20,90 37,50 54,10	21,30 37,90 54,50	16,59	1,7	15	2270 4540 6810	2500 4994 7491	454 908 1362	0,93 1,84 2,77
12B-1 12B-2 12B-3	19,05	11,68	12,07	5,72	22,50 42,00 61,50	24,20 43,60 63,10	25,20 44,50 64,00	19,46	1,85	16	2950 5900 8850	3200 6400 9600	590 1180 1770	1,15 2,31 3,46
16B-1 16B-2 16B-3	25,40	17,02	15,88	8,28	36,10 68,00 99,80	37,40 69,30 101,20	38,40 70,30 102,20	31,88	4,15/3,1	21	4310 8620 12930	5172 10344 15516	862 1724 2586	2,71 5,42 8,13
20B-1 20B-2 20B-3	31,75	19,56	19,05	10,20	41,30 78,80 114,20	----- ----- -----	45,00 81,50 117,90	36,45	4,5 / 3,5	26	6580 13160 19740	7896 15792 23688	1316 2632 3948	3,70 7,20 10,82
24B-1 24B-2 24B-3	38,10	25,40	25,40	14,60	53,40 101,80 150,10	----- ----- -----	57,80 107,10 154,60	48,60	6 / 4,8	33,2	9980 19960 29940	11976 23952 35928	1996 3992 5988	7,10 13,40 20,10
28B-1 28B-2 28B-3	44,45	30,99	27,94	15,90	65,10 124,60 184,20	----- ----- -----	69,50 129,10 188,70	59,56	7,5 / 6	37	13160 26320 39480	15792 31584 47376	2632 5264 7896	8,50 16,60 24,92
32B-1 32B-2 32B-3	50,80	30,99	29,21	17,80	66,00 124,60 183,20	----- ----- -----	71,00 129,60 188,20	58,5	7,0 / 6,0	42	17240 34480 51720	20688 41376 62064	3448 6896 10344	10,25 21,00 31,56